



SENIOR TECH CO., LTD.

No.165, Kang Ning Street, Hsichih, Taipei Hsien 221, Taiwan.

Tel: +886-2-26950405 Fax: +886-2-26952745

<http://www.senortech.com> E-mail: sales@senortech.com



AMON 15S

2008/03/17

Specification	
LCD Panel	15" TFT
Brightness	250 cd/m ² (350 cd/m ² is also available)
Resolution	1024 x 768(Standard)/ 800 x 600 / 640 x 480
Display Colors	16.2 million
Viewing Angle	Horizontal (Left/Right): Total 130° Vertical (Top/Down): Total 120°
Contrast Ratio	500:1
Video Input	Format: Analog RGB; Sync on green Connector: Mini D-Sub 15-Pin VGA type
On-Screen Display & Controls	Multi-Language Secure Control Buttons: "+", "Menu", "-" & "Auto"
Touch Screen (Selective)	SENIOR Touch - Resistive 5 Wires (Serial/USB)
Speaker	2W 8Ω X2 (R · L)
Power Consumption	36W Max
Power Supply (Internal)	Input: AC 100~240V; 47~63HZ; 1A Max Output: DC 12V ± 5%
Temperature	Operating: 0°~40°C Storage: -20°C~60°C
Humidity	Operating: 20%~80% RH Storage: 5%~95% RH
Dimension	W380 x H346 x D205
Weight	6.2 kg
Mounting Options	75/100 mm VESA mount
Safety Compliance	CE/FCC, UL/CUL, TUV, CCC, IP43
Optional Devices	
Customer Display	VFD / LCD
Magnetic Stripe Card Reader	3 Tracks; ISO; JIS (K/B wedge)
Smart Card Reader	PC/SC Card (Serial)
Fingerprint Reader	Optical Type, 512 dpi (USB)
iButton	64 bits ID only (K/B wedge)
Keypad	40 keypad (K/B wedge)

※NOTE: The product information and specifications are subject to change without notice.