



SENIOR TECH CO., LTD.

No.165, Kang Ning Street, Hsichih, Taipei Hsien 221, Taiwan.

Tel: +886-2-26950405 Fax: +886-2-26952745

http://www.senortech.com E-mail:sales@senortech.com

APOS 700



2011/03/01

Name	Specification	
Main Board	GST479	
CPU Supports	Intel D410 1.66GHz, w/ 512KB Cache	
System Memory	Two SODIMM DDR2 socket / 1GB up to 4GB DDR2 667/800	
Display Function	CPU Built-in Dynamic Video Memory up to 224MB shared with system	
LCD Touch Panel		
LCD Size	15" TFT LCD	
Resolution	1024 x 768	
Brightness	250 cd/m ² / 350 cd/m ²	
Touch Screen	Five-wire Resistive Touch / Infrared Touch	
Connectivity		
SATA	SATA: 1 x socket for HDD	
LAN	1 x RJ-45 LAN port 10/100/1000 Mbps	Internal 802.11 b/g/n Wireless LAN (Option)
USB	4x External USB ports	
External Serial	2X RJ45 for COM1 COM2	
Internal Serial	COM 5 for VFD, COM6 for Touch Panel	
VGA	1x VGA Port , Support Dual Display	
Parallel	1 x Mini Printer Port	
PS/2 KB	1 x Mini Din Jack	
Mechanical & Environment		
Dimension (W X D X H)	380 X 218 X 354 mm	
Weight	N.W. 7.1Kgs	
Splash Resistant	IP43	
Safety Certifications	FCC / CE / CCC / CB / VDE	
Storage temperature	-20°C ~60°C	
Operating temperature	0°~40°C	
Relative Humidity	20%-80% (non-condensing)	
Software		
Operation System	Windows XP /POS Ready/ Business Vista / Windows 7	
Self-testing program	Observer software	
Peripheral Options		
Magnetic Card Reader	Single Track, Double Tracks, Triple Tracks	
RFID	ISO/IEC 14443A / 13.56MHz	
Smart Card Reader	ISO-7816 compatible	
Finger Print Sensor	Optical Type, 512 dpi	
I-button	Dallas Key	
Modem	56 Kbps Modem	
Webcam	1.3 mega pixels, w/ microphone	
Customer Display	VFD 20x2 lines Display / LCD Graphic Display	

※NOTE: The product information and specifications are subject to change without notice.