



SENOR TECH CO., LTD.

No.165, Kang Ning Street, Hsichih, Taipei Hsien 221, Taiwan.
Tel: +886-2-26950405 Fax: +886-2-26952745
<http://www.senortech.com> E-mail: sales@senortech.com



KDS 66G/ 66T
Kitchen Display System

2009/10/07

Name	Specification	
Main Board	GST-388	
CPU Supports	Intel Atom N270 1.6GHz, w/ 512KB Cache	
System Memory	Two SODIMM DDR2 socket / 1GB up to 2GB DDR2 533	
Display Function	Intel 945GSE Chipset Dynamic Video Memory up to 224MB shared with system	
LCD Touch Panel		
LCD Size	15" TFT LCD	
Resolution	1024 x 768	
Brightness	250 cd/m ² / 350 cd/m ²	
Touch Screen	5-wire Resistive Touch (KDS 66T) Glass only (KDS 66G)	
Connectivity		
SATA/IDE	SATA: 1 x socket for HDD / 1x Compact Flash socket	
LAN	1 x RJ-45 LAN port 10/100/1000 Mbps	Internal 802.11g Wireless LAN (Option)
USB	3x External USB ports	
Parallel	1 x Mini Printer Port	
PS/2 KB	1 x Mini Din Jack	
Audio	1 X Earphone Jack For Line- out	
Mechanical & Environment		
Dimension (W X D X H)	389 x 96 x 334mm	
Weight	7 Kg	
Fanless & Ventless	Aluminum Casing, Fanless & Ventless System	
Infrared Function	Built-in Infrared K/B & Mouse Receiver(Optional)	
Splash Resistant	IP66	
Safety Certifications	FCC / CE / CCC / TUV / CB	
Storage temperature	-20°C ~60°C	
Operating temperature	0°~40 °C	
Relative Humidity	20%-90% (non-condensing)	
Software		
Operation System	Windows 2000 / XP / Business Vista	
Self-testing program	SENOR self-testing software	
Peripheral Options		
Infrared keyboard	Keyboard wedge interface	

※NOTE: The product information and specifications are subject to change without notice.