



SE NOR TECH CO., LTD.

No.165, Kangning Street, Xizhi District, New Taipei City 22150, Taiwan

Tel: +886-2-26950405 Fax: +886-2-26952745

<http://www.senortech.com> E-mail: sales@senortech.com

iSPOS 255



2013/07/05

Specifications		
Model number	iSPOS 255P	iSPOS 255V
CPU Supports	Intel D2550 Dual Core 1.8GHz	
System Memory	2 * SO-DIMM Sockets,DDR3-1066, Max. 4GB	
LCD Touch Panel		
LCD Size	15" TFT LCD	
Resolution	1024 * 768	
Brightness	250 cd/m ² or 350 cd/m ²	
Touch Screen	5-wire Resistive Touch or Capacitive Touch or FRT or PCT	
Connectivity		
SATA	1 for 2.5" HDD or SSD	
LAN	1 * RJ-45 LAN port 10/100/1000 Mbps	
USB	5	
External Serial	2 *RJ45 for COM + 1 * RJ11 for Cash Drawer	
Internal Serial	COM 1 for VFD, COM2 for Touch Panel	
Parallel	1 * DB25	N/A
VGA	N/A	1 * DB15 for Video-out
PS/2 KB	1	
Audio	1 * Line-out Jack	
Mic	1 * Mic-in Jack	
Mechanical & Environment		
Dimensions (W * D * H)	389 * 232 * 363 mm	
Weight	8.5 Kgs	
Splash Resistant	IP 66	
Fanless & Ventless	Aluminum Casing, Fanless & Ventless System	
Safety Certifications	FCC / CE	
Storage temperature	-20°C~60°C	
Operating temperature	0°C~40°C	
Relative Humidity	10%~90% (non-condensing)	
Power Consumption	60 W maximum	
Software		
Operation System	Win 7, POSReady 7	
Self-testing Program	SE NOR Observer Utility	
Peripheral Options		
3G	WCDMA 850/ 1900/ 2100 MHz EDGE/ GPRS/ GSM 850/ 900/ 1800/ 1900 MHz	
Wi-Fi	802.11 b/g/n Wireless LAN	
Magnetic Card Reader	Single Track, Double Tracks, Triple Tracks	
Smart Card Reader	ISO-7816 Compatible	
Contactless Card Reader	RFID (ISO/IEC 14443A / 13.56 MHz / Mifare S50)	
Fingerprint Sensor	Optical Type, 512 dpi	
I-button	Dallas Key	
Customer Display	VFD 20 * 2 lines Display / LCD Graphic Display	

※NOTE: The product information and specifications are subject to change without notice.