



SENIOR TECH CO., LTD.

No.165, Kangning Street, Xizhi District, New Taipei City 22150, Taiwan

Tel: +886-2-26950405 Fax: +886-2-26952745

<http://www.senortech.com> E-mail: sales@senortech.com



iSPOS WP 750

2011/12/27

Specifications	
Main Board	GST-390E
CPU Supports	Intel D525 Dual Core 1.80GHz, 1MB L2 Cache
System Memory	2 x SO-DIMM Sockets, 200-pin DDR3-800, Max. 4GB
Display Function	Intel GMA 3150 share system memory up to 256MB
LCD Touch Panel	
LCD Size	15" TFT LCD
Resolution	1024 x 768
Brightness	250 cd/m ² or 350 cd/m ²
Touch Screen	Five-wire Resistive Touch, Capacitive Touch
Connectivity	
SATA/IDE	SATA: 1 x socket for HDD / IDE: 1 x Compact Flash socket
LAN	1 x RJ-45 LAN Port 10/100/1000 Mbps
USB	3 x External USB Ports, 1 x Internal USB port for Thermal Printer
External Serial	2 x DE9 for COM, 1 x RJ11 for Cash Drawer
Internal Serial	COM 1 for VFD, COM2 for Touch Panel
PS/2 KB	1 x Mini Din Jack
Mechanical & Environment	
Dimensions (W X D X H)	389 x 232 x 464 mm
Weight	15 Kgs
Splash Resistant	IP 43
Fanless & Ventless	Aluminum Casing, Fanless & Ventless System
Safety Certifications	FCC / CE
Storage temperature	-20°C~60°C
Operating temperature	0°C~40°C
Relative Humidity	10%~90% (non-condensing)
Power Consumption	60 W maximum for MIKI 750, 60 W maximum for internal thermal printer (GTP-250)
Software	
Operation System	Win XP, Win XP Embedded, WEPOS, POSReady 2009, VISTA, Win 7, POSReady 7, Linux Kernel 2.6
Self-testing Program	SENIOR Observer Utility
Printer	
Internal Thermal Printer (GTP-250)	Dot Density, 7dots/ mm
	Printing Speed 47 lines/sec, 200mm/sec
	Buffer, 4 Kbytes
	Paper Roll width, 80 mm
Interface	USB, Parallel/Serial/Ethernet (Optional)
Peripheral Options	
3G	WCDMA 850/ 1900/ 2100 MHz EDGE/ GPRS/ GSM 850/ 900/ 1800/ 1900 MHz
Wi-Fi	802.11 b/g/n Wireless LAN
Magnetic Card Reader	Single Track, Double Tracks, Triple Tracks
Smart Card Reader	ISO-7816 Compatible
Contactless Card Reader	RFID (ISO/IEC 14443A / 13.56 MHz / Mifare S50)
Finger Print Sensor	Optical Type, 512 dpi
I-button	Dallas Key
Customer Display	VFD 20 x 2 lines Display / LCD Graphic Display

※NOTE: The product information and specifications are subject to change without notice.