



SENIOR TECH CO., LTD.

No.165, Kangning Street, Xizhi District, New Taipei City 22150, Taiwan

Tel: +886-2-26950405 Fax: +886-2-26952745

<http://www.senortech.com> E-mail: sales@senortech.com

iSPOS 104



2011/12/27

| Specifications | | |
|-------------------------------------|---|------------------------------|
| Model | iSPOS 104 | |
| Main Board | GST288 | |
| CPU Supports | Intel D425 Single Core 1.80GHz, 512K L2 Cache | |
| System Memory | 2 x SO-DIMM Sockets, 200-pin DDR3-800, Max. 4GB | |
| Display Function | Intel GMA 3150 share system memory up to 256MB | |
| LCD Touch Panel | | |
| LCD Size | 10.4" TFT LCD | |
| Resolution | 800 x 600 | |
| Brightness | 230 cd/m ² or 300 cd/m ² | |
| Touch Screen | Five-wire Resistive Touch or Projected Capacitive Touch | |
| Connectivity | | |
| SATA/IDE | SATA: 1 x socket for SSD | |
| LAN | 1 x RJ-45 LAN port 10/100/1000 Mbps | |
| USB | 2 x External USB ports | |
| External Serial | Options: Mini PCIe card (COM 4) | |
| Internal Serial | COM1 for Touch Panel | |
| VGA | N/A | 1 x DFC 20-pin for Video-out |
| PS/2 KB | 1 x Mini Din Jack | |
| Speaker | 2 built-in speakers | |
| Mechanical & Environment | | |
| Dimensions (W X D X H) | Desktop: 276 x 155 x 380 mm (Without Card Reader: 276 x 155 x 355mm) Wall Mount: 276 x 60 x 260 mm (Without Card Reader: 276 x 60 x 235mm) | |
| Weight | TBD | |
| Splash Resistant | IP 66 | |
| Fanless & Ventless | Aluminum Casing, Fanless & Ventless System | |
| Safety Certifications | FCC / CE | |
| Storage temperature | -20°C~60°C | |
| Operating temperature | 0°C~40°C | |
| Relative Humidity | 10%~90% (non-condensing) | |
| Power Consumption | 40 W maximum | |
| Software | | |
| Operation System | Win XP, Win XP Embedded, VISTA, Win 7, Linux Kernel 2.4~2.6 Win CE 6.0/7.0(.Net Framework 3.5) , Android 3.0 | |
| Self-testing Program | SENIOR Observer Utility | |
| Peripheral Options | | |
| 3G | WCDMA 850/ 1900/ 2100 MHz EDGE/ GPRS/ GSM 850/ 900/ 1800/ 1900 MHz | |
| Wi-Fi | 802.11 b/g/n Wireless LAN | |
| Magnetic Card Reader | Single Track, Double Tracks, Triple Tracks | |
| Contactless Card Reader | RFID (ISO/IEC 14443A / 13.56 MHz / Mifare S50) | |
| Customer Display | LCD Graphic Display (iSMON 8) | |

※NOTE: The product information and specifications are subject to change without notice.