



# SE NOR TECH CO., LTD.

No. 165, Kangning Street, Xizhi District, New Taipei City 22150, Taiwan.

Tel:+886-2-26950405 Fax:+886-2-26952745

<http://www.senortech.com> E-mail:[sales@senortech.com](mailto:sales@senortech.com)

## APOS 750



Specification	
CPU Supports	Intel D525 Dual core 1.8GHz
System Memory	2 * SO-DIMM Sockets, 200-pin DDR3-800, Max. 4GB
<b>LCD Touch Panel</b>	
LCD Size	15" TFT LCD
Resolution	1024 * 768
Brightness	250 cd/m <sup>2</sup>
Touch Screen	Five-wire Resistive Touch
<b>Connectivity</b>	
SATA	1 for 2.5" HDD or SSD
LAN	1 * RJ-45 LAN port 10/100/1000 Mbps
USB	4
External Serial	2 * DB9
Internal Serial	COM 5 for VFD, COM6 for Touch Panel
VGA	1
Parallel	1
PS/2 KB	1
<b>Mechanical &amp; Environment</b>	
Dimension (W * D * H )	380 * 218 * 354 mm
Weight	7.1Kgs
Splash Resistant	IP43
Safety Certifications	FCC / CE / CCC / CB
Storage temperature	-20°C~60°C
Operating temperature	0°C~40°C
Relative Humidity	20%-80% (non-condensing)
<b>Software</b>	
Operation System	Win XP, Win XPE, POSReady 2009, Win 7, POSReady 7, Linux Kernel 2.6
Self-testing program	Observer software
<b>Peripheral Options</b>	
Magnetic Card Reader	Single Track, Double Tracks, Triple Tracks
RFID	ISO/IEC 14443A / 13.56MHz
Smart Card Reader	ISO-7816 compatible
Finger Print Sensor	Optical Type, 512 dpi
I-button	Dallas Key
Customer Display	VFD 20*2 lines Display / LCD Graphic Display

※**NOTE:** The product information and specifications are subject to change without notice.