



SENOR TECH CO., LTD.

No.165, Kang Ning Street, Hsichih, Taipei Hsien 221, Taiwan.

Tel: +886-2-26950405 Fax: +886-2-26952745

http://www.senortech.com E-mail:sales@senortech.com



iSMON 15G/ 15S

Water & Dust Proof Display

2009/03/17

Name	Specification
LCD Panel	15" TFT
Brightness	250 cd/m ² (350 cd/m ² is also available)
Resolution	1024 x 768 / 800 x 600 / 640 x 480
Display Colors	16.2 million
Viewing Angle	Horizontal (Left/Right): Total 130° Vertical (Top/Down): Total 120°
Contrast Ratio	500:1
Video Input	Format: Analog RGB; Sync on green Connector: Mini D-Sub 15-Pin VGA type
On-Screen Display & Controls	Multi-Language Secure Control Buttons: "+", "Menu", "-", "& "Auto"
Touch Screen	5-wire Resistive Touch (iSMON 15S) Glass only (iSMON 15G)
Speaker	2W 8Ω X2 (R、L)
Power Consumption	36W Max
Power Supply (Internal)	Input: AC 100~240V; 47~63HZ; 1A Max Output: DC 12V ± 5%
Temperature	Operating: 0°~40°C Storage: -20°C~60°C
Humidity	Operating: 20%-80% RH Storage: 5%-95% RH
Dimension (W X D X H)	389 x 232 x 363mm
Color	Black / Silver
Weight	7 kg/ Aluminum Casing
Mounting Options	75mm/ 100mm VESA mount
Water& Dust Proof	IP66 / Ventless design
Safety Compliance	CE/FCC

※NOTE: The product information and specifications are subject to change without notice.