



SE NOR TECH CO., LTD.

No.165, Kang Ning Street, Hsichih, Taipei Hsien 221, Taiwan.  
Tel: +886-2-26950405 Fax: +886-2-26952745  
http://www.senortech.com E-mail:sales@senortech.com



iSPOS 855

2010/07/30

Name	Specification
Main Board	GST-390D
CPU Supports	Intel D510 dual Core 1.66GHz, w/ 1MB Cache
System Memory	Two SODIMM DDR2 socket supports (Notebook type 200-Pin) Supports DDR2 667/800 DIMM Max.4GB
Display Function	CPU integrated graphic
Capacitor	Solid type
<b>LCD Touch Panel</b>	
LCD Size	15" TFT LCD
Resolution	1024 x 768
Brightness	250 cd/m <sup>2</sup> / 350 cd/m <sup>2</sup>
Touch Screen	ELO or SENOR five-wire Resistive Touch / Capacitive touch
<b>Connectivity</b>	
SATA/IDE	SATA: 1 x socket for HDD / 1x Compact Flash socket
LAN	1 x RJ-45 LAN port   Internal 802.11g Wireless LAN (Option) 10/100/1000 Mbps
USB	3x External USB ports
External Serial	4X RJ45 for COM or 2 X RJ45 for COM + 2 X RJ11 for Cash Drawer
Internal Serial	COM 1 for VFD, COM2 for Touch Panel
Parallel	1 x Mini Printer Port
VGA / Printer Port	iSPOS 855 P (mini-printer port) / iSPOS 855 V (VGA port)
PS/2 KB	1 x Mini Din Jack
Audio	1 X Earphone Jack For Line- out
<b>Mechanical &amp; Environment</b>	
Dimension (W X D X H )	389 X 232 X 363 mm
Weight	8.5 Kg
Fanless & Ventless	Aluminum Casing, Fanless & Ventless System
Infrared Function	Built-in Infrared K/B & Mouse Receiver(Optional)
Splash Resistant	IP66(IP43 with card reader)
Safety Certifications	FCC / CE / CCC / TUV / CB
Storage temperature	-20°C ~60°C
Operating temperature	0°-40 °C
Relative Humidity	10%-90% (non-condensing)
<b>Software</b>	
Operation System	Win 2000 / XP Pro XP Embedded , Linux Kernel 2.4~2.6, Business Vista, Windows 7, WEPOS, POS Ready
Self-testing program	SE NOR Diagnostic
<b>Peripheral Options</b>	
Infrared keyboard	Keyboard wedge interface
Magnetic Card Reader	Single Track, Double Tracks, Triple Tracks
Contactless Card Reader	RFID (ISO/IEC 14443A / 13.56MHz)
Smart Card Reader	ISO-7816 compatible
Finger Print Sensor	Optical Type, 512 dpi
I-button	Dallas Key
Customer Display	VFD 20x2 lines Display / 7" LCD Graphic Display

※NOTE: The product information and specifications are subject to change without notice.