



SE NOR TECH CO., LTD.

No.165, Kangning Street, Xizhi District, New Taipei City 22150, Taiwan
 Tel: +886-2-26950405 Fax: +886-2-26952745
<http://www.senortech.com> E-mail: sales@senortech.com

iSPOS 105



| Specifications | |
|-------------------------------------|---|
| CPU Supports | Intel D2550 Dual Core 1.80GHz |
| System Memory | 2 * SO-DIMM DDR3-1066, Max. 4GB |
| LCD Touch Panel | |
| LCD Size | 10.4" LED backlight |
| Resolution | 1024 x 768 |
| Brightness | 400 cd/m ² |
| Touch Screen | FRT or PCT |
| Connectivity | |
| SATA SSD | 32G (default)/ 64G(option) |
| LAN | 1 * RJ-45 LAN port 10/100/1000 Mbps |
| USB | 2 * External USB ports |
| Internal Serial | 2 * RJ-45 for COM |
| Speaker | 2 * built-in speakers |
| Mechanical & Environment | |
| Dimensions (W * D * H) | Desktop: 280 * 165 * 255 mm (Without Card Reader: 280 * 165 * 230mm) Wall Mount: 280 * 50 * 380 mm (Without Card Reader: 280 * 50 * 345mm) |
| Weight | 3.0 Kgs |
| Splash Resistant | IP 66 |
| Fanless & Ventless | Aluminum Casing, Fanless & Ventless System |
| Safety Certifications | FCC / CE |
| Storage temperature | -20°C~60°C |
| Operating temperature | 0°C~40°C |
| Relative Humidity | 10%~90% (non-condensing) |
| Power Consumption | 40 W maximum |
| Software | |
| Operation System | Win 7, Win POSReady 7 |
| Self-testing Program | SE NOR diagnostics Utility |
| Peripheral Options | |
| VGA Cable | 1 * External VGA |
| 3G GPRS | WCDMA 850/ 1900/ 2100 MHz EDGE/ GPRS/ GSM 850/ 900/ 1800/ 1900 MHz |
| Wi-Fi | 802.11 b/g/n Wireless LAN |
| Magnetic Card Reader | Single Track, Double Tracks, Triple Tracks |
| Contactless Card Reader | RFID (ISO/IEC 14443A / 13.56 MHz / Mifare S50) |
| Customer display | 2*20 lines display-VFD |

※NOTE: The product information and specifications are subject to change without notice.